



RX10 FULLY RUGGED TABLET

- Intel °Core™ M vPro™ Processor
- Premium Thin and Light design weighs 1.2kg and 18.8mm thin
- 10.1" Full HD LumiBond * 2.0 display with Getac sunlight readable technology and capacitive touchscreen
- 2-in-1 design for mobility as a tablet or productivity with the attached keyboard
- Getac's proprietary SnapBack add-on featuring kickstand and hand strap, smartcard reader or detachable keyboard















Specifications

Operating System Windows 10 Pro

Mobile Computing Platform

Platform Options:

Intel[®] Core [™] M-5Y10c Processor 0.8 GHz Max. 2.0GHz with Intel [®] Turbo Boost Technology -4MB Intel * Smart Cache

Intel® Core® M-5Y71 vPro ® Processor 1.2 GHz Max. 2.9GHz with Intel ® Turbo Boost Technology -4MB Intel® Smart Cache

Intel® HD Graphics 5300

10.1" IPS TFT LCD FHD (1920 x 1200) 800 nits LumiBond * display with Getac sunlight readable technology Capacitive multi-touch screen

Storage & Memory

4GB LPDDR3 expandable to 8GB Optional SSD 128GB / 256GB / 512GB

6 tablet buttons (Windows, Power, Function Key 1, Function Key 2, Barcode Reader Trigger, Volume Up, Volume Down)

Pointing Device

Touchscreen

- Capacitive multi-touch screen
- Optional dual mode touchscreen (multi-touch and digitizer)

Expansion Slot

Optional 1D/2D imager barcode reader

I/O Interface

HD webcam x 1 8M pixels auto focus rear camera x 1 Headphone out / mic-in combo x 1 DC in Jack x 1 USB 3.0 (9-pin) x 1 USB 2.0 (4-pin) x 1 Docking connector (16-pin) x 1 Micro HDMI x 1 Optional RF antenna pass-through for GPS, WLAN and WWAN

Communication Interface

Intel[®] Dual Band Wireless-AC 7265, 802.11ac Bluetooth (v4.0) ⁱ Optional dedicated GPS

Optional 4G LTE mobile broadband

Security Feature

TPM 2.0

Optional Intel* vPro* Technology Optional fingerprint scanner or HF RFID reader Optional SnapBack add-on: Hand Strap & Kick Stand & Smart Card Reader

Optional SnapBack add-on: Hand Strap & Kick Stand & Smart Card Reader & Detachable

AC adapter (65W, 100-240VAC, 50 / 60Hz) Li-lon battery (15.2V, 2160mAh) LifeSupport battery swappable technology Optional High Capacity Battery with Smart Card reader Expansion (14.4V, 5800mAh)

Dimension (W x D x H) & Weight

280 x 245 x 18.8 mm (11" x 9.65" x 0.74") 1.2kg (2.65 lbs)

Rugged Feature

MIL-STD-810G certified and IP65 certified MIL-STD-461F certified v 4 feet drop resistant Vibration & drop resistant e-Mark certified for vehicle usage Optional ANSI/ISA 12.12.01

Environmental Specification

Temperaturevii:

- Operating: -21°C to 55°C / -5.8F to 131°F
- Storage: -51°C to 71°C / -60°F to 160°F
- 95% RH, non-condensing

Software

Getac Utility Getac Camera Adobe® Reader® Getac Barcode Manager
Optional Absolute DDS® Persistence

Main battery (15.2V, 2160mAh) High Capacity battery (14.4V, 5800mAh) Multi-Bay Charger (Dual Bay) Multi-Bay Charger (Eight Bay) AC adapter (65W, 100-240VAC) Vehicle adapter (90W, 11-16V DC and 22-32V DC) Capacitive stylus Digitizer Pen Shoulder strap (2-point) Hand Strap & Kick Stand Hand Strap & Kick Stand & Smart Card Reader Hand Strap & Kick Stand & Smart Card Reader & Detachable Keyboard Bracket w/ Rotating Hand Strap Kick Stand Vehicle dock Office dock Protection film

Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment

That is why Getac has introduced accidental damage as standard under our new Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper.

- Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is
- operating in the area. HF RFID and Fingerprint scanner are mutually exclusive options.

 13.56MHz Contactless HF RFID/NFC reader
- (ISO 15693, 14443 A/B, Mifare and FeliCa compliant).
- Battery life testing conducted under MobileMark 2007. Battery performance will vary upon software applications, wireless settings, power management settings, LCD brightness, customized modules and environmental conditions. The battery has a limited number of charge cycles and may eventually need to be replaced by a Getac service provider. Battery life and charge cycles vary by use and settings. Weight and dimensions vary from
- configurations and optional accessories. MIL-STD-461F 90W AC adapter sold
- separately.
- Tested by a national independent third party test lab following MIL-STD-810G.

Fully Rugged Tablet



Docking Solutions

	Vehicle Dock	Office Dock
Serial Port	1	
External VGA		1
DC in Jack	1	1
USB	2	4
LAN	1	1
HDMI		1



NOYA BİLGİSAYAR SİSTEMLERİ VE DANIŞMANLIK SANAYİ VE TİCARET LTD. ŞTİ.

Tel. 0212 294 24 03 - 0850 399 66 92

Fax. 0212 294 06 88

info@noyabilgisayar.com

Adres

Hamidiye Mah. Soğuksu Cad. No:5 K:8 Kağıthane 34408, İstanbul